

Trade name: SD-600

TDS

Wudi De Xin Chemical Co. Ltd.

Address: High-tech Zone Wudi County, Shandong, China
Tel: 86-543-6452566

P.C. 251909
Fax: 86-543-6452566

Description

SD-600 polyol is a unique grafted polyether polyol containing copolymerized styrene and acrylonitrile, its solid content is 40~44%. It is manufactured without the use of BHT. SD-600 polyol is designed for use in the manufacture of high resiliency flexible molded foam, high comfort flexible foam and semi-flexible molded foam. It can be used to produce high-load-bearing foams over a wide density range. SD-600 can be used in formulations utilizing all TDI, TDI /Polymeric MDI blends or all Polymeric MDI compositions.

Characteristic data

Typical Properties	Units	Limits	Test Methods
Hydroxyl value	mg KOH/g	19.0~23.0	GB/T 12008.3-2000
Water, max.	%	0.05	GB/T 22313-2008
pH		5~7	GB/T 12008.2-2010
Viscosity	mpa.s(25°C)	4000~6000	GB/T 12008.7-2010
Appearance / physical state		White viscous liquid	Q/SH 1065 002-2010

Package:

200KG in iron drum

Precaution:

Keep containers tightly closed so as to protect them from rays of light and moisture.
