

**Trade name: SE-2014**

**TDS**

**Wudi De Xin Chemical Co. Ltd.**

Address: High-tech Zone Wudi County, Shandong, China  
Tel: 86-543-6452566

P.C. 251909  
Fax: 86-543-6452566

---

**Description**

SE-2014 polyol is a propylene glycol propoxylated polyether polyol with an average molecular weight of 8000 ,BHT and amine free. It is mainly used for elastomer, sealant.

**Characteristic data**

| Typical Properties          | Units      | Limits          | Test Methods       |
|-----------------------------|------------|-----------------|--------------------|
| Hydroxyl value              | mg KOH/g   | 12.5~15.5       | GB/T 12008.3-2009  |
| Water, max.                 | %          | ≤0.05           | GB/T 22313-2008    |
| Acid number, max.           | mgKOH/g    | ≤0.08           | GB/T 12008.5-2010  |
| Colour, max                 | APHA       | ≤50             | GB/T 605-2006      |
| potassium,max               | mg/kg      | /               | GB/T 12008.4-2009  |
| Viscosity                   | mpa.s(25℃) | 2700~3700       | GB/T 12008.7-2010  |
| pH                          |            | 5~7             | GB/T 12008.2-2010  |
| Appearance / physical state |            | liquid, viscous | Q/SH 1065 002-2010 |

**Package:**

200KG in iron drum

**Precaution:**

Keep containers tightly closed so as to protect them from rays of light and moisture.

---