

**Trade name:POP-2015**

**TDS**

**Wudi De Xin Chemical Co. Ltd.**

Address: High-tech Zone Wudi County, Shandong, China  
Tel: 86-543-6452566

P.C. 251909  
Fax: 86-543-6452566

### **Description**

POP-2015 polyol is a unique grafted polyether polyol containing copolymerized styrene and acrylonitrile, its solid content is 13~17%. It is manufactured without the use of BHT. POP-2015 polyol is designed for use to increase foam hardness in the manufacture of slabstock foam and VE memory foam. It can be used to produce high-load-bearing foams over a wide density range. POP-2015 can be used in formulations utilizing all TDI, TDI /Polymeric MDI blends or all Polymeric MDI compositions.

### **Characteristic data**

Typical Properties	Units	Limits	Test Methods
Hydroxyl value	mg KOH/g	38~42	GB/T 12008.3-2000
Water, max.	%	0.08	GB/T 22313-2008
pH		5~8	GB/T 12008.2-2010
Viscosity	mpa.s(25°C)	1400~2000	GB/T 12008.7-2010
Appearance / physical state		White viscous liquid	Q/SH 1065 002-2010

### **Package:**

200KG in iron drum

### **Precaution:**

Keep containers tightly closed so as to protect them from rays of light and moisture.

---