

Trade name:POP-2010

TDS

Wudi De Xin Chemical Co. Ltd.

Address: High-tech Zone Wudi County, Shandong, China
Tel: 86-543-6452566

P.C. 251909
Fax: 86-543-6452566

Description

POP-2010 polyol is a unique grafted polyether polyol containing copolymerized styrene and acrylonitrile, its solid content is 10%. It is manufactured without the use of BHT. POP-2010 polyol is designed for use to increase foam hardness in the manufacture of slabstock foam and VE memory foam. It can be used to produce high-load-bearing foams over a wide density range. POP-2010 can be used in formulations utilizing all TDI, TDI /Polymeric MDI blends or all Polymeric MDI compositions.

Characteristic data

| Typical Properties | Units | Limits | Test Methods |
|-----------------------------|-------------|----------------------|--------------------|
| Hydroxyl value | mg KOH/g | 48.5~52.6 | GB/T 12008.3-2000 |
| Water, max. | % | 0.08 | GB/T 22313-2008 |
| pH | | 5~8 | GB/T 12008.2-2010 |
| Viscosity | mpa.s(25°C) | 540~900 | GB/T 12008.7-2010 |
| Appearance / physical state | | White viscous liquid | Q/SH 1065 002-2010 |

Package:

200KG in iron drum

Precaution:

Keep containers tightly closed so as to protect them from rays of light and moisture.
